

# BJ152



# DOUBLE-TAPERED STRAPS




**BJ152** -08063~20200



**BJ152** -24200, 24250



**BJ152** -08063~20200



**BJ152** -24200, 24250

Type	Body
<b>BJ152</b> -08063~20200	Steel (S45C) Quenched and tempered Black oxide finish
<b>BJ152</b> -24200, 24250	Steel (S45C) Coated finish

Part Number	L	W	H	d	L <sub>1</sub>	H <sub>1</sub>	Clamping Force (kN)*	Allowable Screw Torque (N·m)	Weight (kg)			
<b>BJ152-08063</b>	63	25	12	9	25	7	6.9	22	0.1			
<b>BJ152-08080</b>	80				32				0.15			
<b>BJ152-08100</b>	100		16	0.24								
<b>BJ152-10063</b>	63	25	12	11	25	7	8.5	34	0.1			
<b>BJ152-10080</b>	80				32				0.18			
<b>BJ152-10100</b>	100		16	0.22								
<b>BJ152-10125</b>	125	32	19	13	45	13	12.5	50	0.48			
<b>BJ152-10160</b>	160				50				0.64			
<b>BJ152-12063</b>	63		32	16	13	25			10	14.8	71	0.18
<b>BJ152-12080</b>	80	32				0.2						
<b>BJ152-12100</b>	100	19		13	40	13	16.7	80	0.34			
<b>BJ152-12125</b>	125				45				0.46			
<b>BJ152-12160</b>	160	25		0.8								
<b>BJ152-16080</b>	80	32		16	17	25	10	11	70	0.22		
<b>BJ152-16100</b>	100		32			0.42						
<b>BJ152-16125</b>	125		38	19	17	40	13			18	115	0.53
<b>BJ152-16160</b>	160	25				0.9						
<b>BJ152-20100</b>	100	38		19	21	32	13	15	120			0.4
<b>BJ152-20125</b>	125		25			15				40	15	19.7
<b>BJ152-20160</b>	160			50	0.85							
<b>BJ152-20200</b>	200		50	30	26	63	-	22.9	183	1.54		
<b>BJ152-24200</b>	200					30				-	54	-
<b>BJ152-24250</b>	250			35	-	79	-			29.9~52.8	3.85	

\*) The values of **BJ152** -24200 and 24250 show clamping forces at max. - min. protrusion.

## Note

The color of **BJ152** -24200 and 24250 can vary from the production lot.